



Infection Prevention with Confidence!



In the war against microbes, Accel® Disinfectants are the first line of defense for Infection Prevention. Accel® provides comfort and confidence that commonly touched surfaces and instruments are rendered safe to use.

Accel WASH is an instrument and cart cleaning solution for use in pre-soak, manual, ultrasonic applications and automatic washers. Accel Wash's versatile formulation has the ability to clean all soil types present on medical devices and instruments without the use of enzymes. The Stabilized Hydrogen Peroxide in Accel Wash also has the added benefit of providing bacteriostatic properties by helping to control the bacterial growth.

DIRECTIONS FOR USE

MANUAL CLEANING: Dilute Accel Wash at 1:128 at 20°C into a container. Place instruments into the solution for 3 to 5 minutes using agitation when required. Remove the instruments, rinse with potable water, inspect for cleanliness and proceed with the appropriate disinfecting step. Change solution daily or as needed.

ULTRASONIC: Dilute Accel Wash at 1:64 at 20°C into an ultrasonic machine holding tank (Note: The use of hot water is not recommended). Place the instruments into the ultrasonic machine and run for 3 to 5 minutes. Remove the instruments, rinse with potable water, inspect for cleanliness and proceed with the appropriate disinfecting step. Change solution daily or as needed.

AUTOMATIC MACHINE PROCESSING: Dosing may be manually or automatically fed. For use with heated water up to 60°C (140°F). Dilute Accel Wash at 1:128. Place instruments into the solution for a 5 minute cycle time. Change solution for each automatic wash cycle.

CART WASHING: Dosing may be manually or automatically fed. For use with heated water up to 60°C (140°F). Dilute Accel Wash at 1:128. Change solution for each automatic wash cycle.

NOTICE TO USER: Accel WASH is not a holding solution. Accel Wash may not be suitable for all items. Please ensure that the instruments, equipment or device material is compatible with Accel Wash. Compatible materials include acrylic, rubber, low and High Density plastics and rigid stainless steel. Accel Wash is not recommended for use on copper, brass, anodized aluminum, carbon steel and some coatings. If you are uncertain as to the material composition of your item, confirm with the manufacturer before proceeding or visit the Compatibility Section on www.virox.com for a list of compatible materials.

Accel WASH

Product Number	ACCWAS4, ACCWAS20*
Concentration of Active	3% Hydrogen Peroxide
Container Size	4L
Dilution	1:64 (Ultrasonic Cleaning) 1:128 (Manual, Cart or Automatic Machine Cleaning)
	*special order item



Engineering Revolutionary Disinfectants for the War Against Microbes

1 (800) 387-7578
www.virox.com